

# PX3 SERIES

Bluetooth® Differential Pressure/Air Velocity Transducers



PX3

The PX3 transducer can measure either air pressure or velocity with the flip of a switch. The PX3 is available in three installation configurations: duct, panel or universal. Duct and panel models have two pressure and velocity options: 0-1 in. WC / 0-3,000 ft/min or 1-10 in. WC / 3,000-6,000 ft/min with four field-selectable sub-ranges. The universal model comes in one pressure/velocity range: 0-10 in. WC / 0-7,000 ft/min with seven field-selectable sub-ranges for pressure and eight for velocity. All variants are available with and without display. The PX3 has an IP65/NEMA 4 environmental rating and a 5-year limited warranty.

The Veris Sensors App provides the ability to connect to a device and configure a variety of field-selectable parameters remotely from a smartphone via Bluetooth wireless technology. The app allows users to create and store commonly used parameters that will reduce commissioning time and provide assurance that all parameters are properly configured with no call backs. The app can also create a trend log while connected, providing important data for troubleshooting purposes. iOS® users can download the app through the iOS App Store on their smart device. Android users can download the app through the Google Play™ store.

**Note: This product is intended for use in HVAC and building environmental control applications. It is not intended for direct medical monitoring of patients.**

## SPECIFICATIONS

### GENERAL

Media Compatibility	Dry air or inert gas
Input Power	Three-wire Volt mode: 24 Vac or 12-30 Vdc* Two-wire mA mode: 12-30 Vdc*
Output Power	Field-selectable: 2-wire, loop-powered 4-20 mA Minimum input voltage for 4 to 20 mA operation: 250 Ω loop = 12 Vdc; 500 Ω loop = 19 Vdc (DC only, clipped and capped), 24 Vac/dc or 3-wire 0-5V/0-10V Minimum load resistance for Volt operation: 5 kΩ

### PRESSURE RANGES

01 Pressure Range	Pressure Mode: Unidirectional: 0.1/0.25/0.5/1 in. WC, switch selectable Bidirectional: ±0.1/±0.25/±0.5/±1 in. WC, switch selectable Unidirectional: 25/50/100/250 Pa, switch selectable Bidirectional: ±25/±50/±100/±250 Pa, switch selectable Velocity Mode: 500/1,000/2,000/3,000 ft/min 2.5/5/10/15 m/s
-------------------	---

## Wireless configuration

View and configure all field-selectable parameters via smartphone. No ladder necessary for duct mount applications.

## High accuracy

High accuracy digital sensor with seven selectable pressure and eight velocity sub-ranges, maintains calibration and reduces callbacks

## Maintenance free

High reliability sensor technology for long-term, maintenance-free operation

## APPLICATIONS

- Duct static pressure (Pressure mode)
- Building or room pressure (Pressure mode)
- Filter status (Pressure mode)
- Air flow measurement (Velocity mode)

## Reduce field failures

Excellent tolerance to overpressure and vibration reduces field failures

## Water-resistant housing

IP65/NEMA 4 housing allows for mounting in wash-down locations

## Circuit protection

Circuit protection avoids damage due to incorrect input wiring

02 Pressure Range	Pressure Mode: Unidirectional: 1.0/2.5/5/10 in. WC, switch selectable Bidirectional: ±1.0/±2.5/±5/±10 in. WC, switch selectable Unidirectional: 250/500/1,000/2,500 Pa, switch selectable Bidirectional: ±250/±500/±1,000/±2,500 Pa, switch selectable Velocity Mode: 3,000/4,000/5,000/6,000 ft/min 15/20/25/30 m/s
05 Pressure Range	Pressure Mode: Unidirectional: 0.1/0.25/0.5/1/2.5/5/10 in. WC, switch selectable Bidirectional: ±0.1/±0.25/±0.5/±1/±2.5/±5/±10 in. WC, switch selectable Unidirectional: 25/50/100/250/500/1,000/2,500 Pa, switch selectable Bidirectional: ±25/±50/±100/±250/±500/±1,000/±2,500 Pa, switch selectable Velocity Mode: 500/1,000/2,000/3,000/4,000/5,000/6,000/7,000 ft/min 2.5/5/10/15/20/25/30/35 m/s
<b>SENSOR</b>	
Response Time	Standard: T95 in 20 sec, Fast: T95 in 2 sec, DIP switch selectable
Mode	Unidirectional or bidirectional, DIP switch selectable
Display (option)	Pressure mode: Signed 3-1/2 digit LCD, indicates pressure, overrange indicator Velocity mode: Signed 4-1/2 digit LCD, indicates velocity, overrange indicator
Proof Pressure	3 psid (20,600 Pa)
Burst Pressure	5 psid (34,500 Pa)
Pressure Mode Accuracy	±1% FS (combined linearity and hysteresis)
Velocity Mode Accuracy	±90 ft/min (±0.45 m/s) plus 5% of measured value**

Note: The Bluetooth word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. Any use of such marks is under license.



## SPECIFICATIONS (CONT.)

### TEMPERATURE EFFECT

Temperature Effect	1" (250 Pa) models: 0.05%/°C; 10" (2,500 Pa) models: 0.01%/°C (Relative to 25 °C) 0 to 50 °C (32 to 122 °F)
Zero Drift (1-year)	1 in. WC (250 Pa) models: 2.5% FS typ.; 10 in. WC (2,500 Pa) models: 0.25% FS typ.
Zero Adjust	Pushbutton auto-zero and digital input (2-pos terminal block)
Operating Env.	-20 to 60 °C (-4 to 140 °F)**
Altitude of Operation	0 to 3,000 m
Humidity Range	100% RH, non-condensing
Mounting Location	For indoor or outdoor use (display will not function below 0 °C (32 °F))
Fittings	Brass barb; 0.24" (6.1 mm) o.d.
Bluetooth Frequency Range	2.402 to 2.480 GHz (Bluetooth version 4.2, enabled by DIP switch)
Environmental Rating	IP65, NEMA 4
Flammability Rating	UL 94 5VA fire retardant polycarbonate, plenum rated


### WARRANTY

Limited Warranty	5 years
------------------	---------

### AGENCY APPROVALS


**CE** EMC Conformance: EN 61000-6-3 and A1, Class B, EN 61000-6-1, EN61326-1 and EN61326-2-3.  
 \* Class 2/II power source.  
 \*\* For measured values between 200 and 7,000 ft/min (1 and 35 m/s).  
 \*\*\* Display will not function below 0 °C (32 °F).

## DIMENSIONAL DRAWING




## SMART PHONE APP

The Veris Sensors App allows for remote viewing and adjustment of settings. A great tool for reducing commissioning time.




## WIRING DIAGRAM

2-wire, 4-20 mA Current Loop Output



## WIRING DIAGRAM

3-wire, 0-5 V/0-10 V Voltage Output



## ORDERING INFORMATION

Enclosure	Local Display	NIST Certificate*	Range	Wireless Technology
PX3 D = Duct P = Panel	L = LCD Display X = No Display	N = NIST X = None	01 = Pressure: 0 to 1 in. WC/ 0 to 250 Pa Velocity: 0 to 3,000 ft/min/ 0 to 15 m/s 02 = Pressure: 1 to 10 in. WC/ 250 to 2500 Pa Velocity: 3,000 to 6,000 ft/min/ 15 to 30 m/s	Blank = Wireless technology enabled model
*8-point calibration				
Example: PX3 [D] [L] [X] [01]				
Enclosure	Local Display	NIST Certificate*	Range	Wireless Technology
PX3U	L = LCD Display X = No Display	N = NIST X = None	05 = Pressure: 0 to 10 in. WC/ 0 to 2,500 Pa Velocity: 0 to 7,000 ft/min / 0 to 35 m/s	Blank = Wireless technology enabled model
*16-point calibration				
Example: PX3U [L] [X] [05]				

## ACCESSORIES

- VFXP Series Air Velocity Measurement Probe\*
- Velocity Pitot Tubes, 8-5/8", 12-5/8", 18-5/8" (AA18, AA19, AA20)\*
- Static-04 Pick-up - 4" Duct Static Pickup Probe (AA06)
- Static-08 Pick-up - 8" Duct Static Pickup Probe (AA07)
- Wall Plate Remote Pickup (AA56)

\*For use with the PX3P (panel) and PX3U (universal) models in Velocity mode only.

